



**NOTES:**

1. MECHANICAL JOINTS FROM TEE TO VALVE AND FROM VALVE TO HYDRANT SHALL BE RESTRAINED WITH MEGALUGS AND STAINLESS STEEL BOLTS.
2. ALL FASTENERS SHALL BE STAINLESS STEEL.
3. HYDRANT EXTENSIONS ARE NOT PERMITTED
4. ALL HYDRANTS, EXCLUDING STORZ CONNECTION, SHALL BE FACTORY PAINTED WITH EPOXY AS IDENTIFIED BELOW:
  - A. PUBLIC (VILLAGE) HYDRANTS SHALL BE MUELLER RED - SHERWIN WILLIAMS POLANE F63RL15
  - B. PRIVATE HYDRANTS ON VILLAGE SYSTEM PRESSURE SHALL BE CAUTION BLUE - SHERWIN WILLIAMS POLANE F63RXL9667
  - C. PRIVATE PRESSURED HYDRANTS ON FIRE LOOPS SHALL BE MUELLER YELLOW - SHERWIN WILLIAMS POLANE F63YL14
5. REFER TO VILLAGE STANDARD SPECIFICATIONS FOR WATER MAIN CONSTRUCTION

SCALE: NTS

**STANDARD HYDRANT ASSEMBLY**

DETAIL: W - 1

DATE: 8-19-19

APPROVED BY: MATT FINEOUR

**VILLAGE OF PLEASANT PRAIRIE**  
 KENOSHA COUNTY, WISCONSIN